MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CROSS POWER 2T
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · **Application of the substance** / **the mixture** Only for proper handling.

Engine oil

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG Bern–Zürich–Strasse 31, Postfach CH–4901 Langenthal Tel. +41 (0)62 919 75 75 www.motorex.com

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- Hazard pictograms Void
- · Sianal word Void
- · Hazard statements Void
- · Additional information:

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	Dangerous components:		
Ī	CAS: 1000172-11-1	Pentadecane, 7-methylene mixed with 1-tetradecene,	10-25%
	EC number: 700-184-9	dimers and trimers, hydrogenated	
	Reg.nr.: 01-0000000547-72		
ſ	EC number: 926-141-6	Hydrocarbons, C11-C14, n-alkanes, isoalkanes,	10-25%
	Reg.nr.: 01-2119456620-43	cycloalkanes, <2% aromatics	
		Asp. Tox. 1, H304, EUH066	
ſ	CAS: 722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched	≥0.25-<1%
	EC number: 682-816-2	alkyl derivs., calcium salts	
		Skin Sens. 1, H317	
_	-	(0.	antd on nogo 3

(Contd. on page 2)

MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 1)

Regulation (EC) No 648/2004 on detergents / Labelling for contents
 aliphatic hydrocarbons ≥15 - <30%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

After eve contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Vapours of this product are heavier than air and will collect in low areas such as pits, storage tanks, and other confined areas.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.

(Contd. on page 3)

MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 2)

Further information about storage conditions:

Store containers closed and protect against rain, dust, heat and other atmospheric influences. Store in cool, dry well ventilated area away from sources of ignition and heat.

- · Storage class: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Goggles recommended during refilling
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:FluidRed

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range Undetermined.
Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 0.6 Vol.% • Upper: 6.5 Vol.%

(Contd. on page 4)



Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 3)

· Flash point: 110 °C

Ignition temperature: >200 °C (DIN 51794)
 Decomposition temperature: Not determined.
 pH Not determined.

· Viscosity:

• Kinematic viscosity 56 mm²/s @ 40 °C

· Consistency

· **Dynamic:** Not determined.

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.

Heat Capacity

• Vapour pressure: Not determined.

Density and/or relative density

• Density at 20 °C: 0.874 g/cm³ (ASTM D 4052)

Relative densityVapour densityNot determined.Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Explosive properties: Product does not present an explosion hazard.

Change in condition

Solidification point: -33 °C

Evaporation rate Not determined.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pvrophoric solids Self-heating substances and mixtures Void · Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 5)

MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 4)

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	· LD/LC50 values relevant for classification: Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics				
Hydrocari					
Oral	LD50	5,000 mg/kg (rat)			
	NOAEL	1,000-5,000 mg/kg/24h (rat)			
Dermal	LD50	2,000 mg/kg (rabbit)			
Inhalative	LC50 / 4h	5.28 mg/l (rat)			
	NOAEL	200 ppm (rat)			
	NOAEC	275-10,400 mg/m3 (rat)			

· 11.2 Information on other hazards

Endocrine disrupting properties

121158-58-5 phenol, dodecyl-, branched

List I

SECTION 12: Ecological information

12.1 Toxicity

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics				
LL50	2-5 mg/l/96h (fish)			
LL50	2-5 mg/l/48h (fish)			
LL50	5-17 mg/l/24h (fish)			
EL50	1.4 mg/l/48h (aquatic invertebrates)			
EL50	4.6 mg/l/24h (aquatic invertebrates)			
	1-3 mg/l/24h (algae / cyanobacteria)			
EL50	1-3 mg/l/72h (algae / cyanobacteria)			
EL50	0.81-0.89 mg/l/21d (aquatic invertebrates)			
NOELR	1.22 mg/l/21d (aquatic invertebrates)			
NOELR	1,000 mg/l/72h (algae / cyanobacteria)			

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water

(Contd. on page 6)

MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 5)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR/RID/ADN, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR/RID/ADN, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR/RID/ADN, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National chemical directories Components listed or exempted from listing:
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

(Contd. on page 7)

MOTOREX
Oil of Switzerland
Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 6)

No special training instructions to ensure protection of human health and environment are required.

· purity requirement

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Abteilung Produktsicherheit

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Skin Sens. 1: Skin sensitisation – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

Annex: Exposure scenario 1

· Short title of the exposure scenario

Industrial use of lubricants and greases in vehicles or machinery

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC16 Heat transfer fluids

PC17 Hydraulic fluids

PC24 Lubricants, greases, release products

Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC7 Use of functional fluid at industrial site

• Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.

Oce Section 1 of the armex to the bally

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

(Contd. on page 8)

MOTOREX*
Oil of Switzerland

Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 7)

- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

· Short title of the exposure scenario

Professional use of lubricants and greases in vehicles or machines

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC16 Heat transfer fluids

PC17 Hydraulic fluids

PC24 Lubricants, greases, release products

· Process category

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC20 Use of functional fluids in small devices

· Environmental release category

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.

(Contd. on page 9)

MOTOREX Oil of Switzerland
Revision: 16.12.2022

Printing date 16.12.2022

Version number 3.1 (replaces version 3.0)

Trade name: CROSS POWER 2T

(Contd. of page 8)

- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of lubricants and greases in vehicles or machines
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category PC24 Lubricants, greases, release products
- · Environmental release category

ERC9a Widespread use of functional fluid (indoor)

ERC9b Widespread use of functional fluid (outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- Air No special measures required.
- · Water No special measures required.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB