

# 2024 RK Chain Specifications and Application Chart



On-Road Series	RK Model	Seal Type	STD	GB	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Superbike &amp; Adventure</b>	520ZXW	XW	○	○	○	○	2.20	2.20	20.9	17.8	42.0	Rivet
	525ZXW		○	○	○	○	2.40	2.60	23.5	20.7	46.4	Rivet
	530ZXW		○	○	○	○	2.60	2.60	25.4	22.2	49.8	Rivet
<b>Street Riding &amp; Touring</b>	428XRE	XW	○	○	○	○	2.00	2.00	22.4/21.0	12.0	27.0	Clip/Rivet
	520XRE		○	○	○	○	2.00	2.00	21.7/19.9	15.6	36.5	Clip/Rivet
	525XRE		○	○	○	○	2.20	2.30	22.5	18.0	42.0	Rivet
	530XRE		○	○	○	○	2.40	2.40	24.5	21.1	44.0	Rivet
<b>Street Riding &amp; Daily Use</b>	420MRU	U	○	○			1.80	1.45	17.1	7.9	22.2	Clip
	428MRU2		○				2.00	2.00	19.2	10.0	27.0	Clip
	520MRU	UW		○			1.80	2.00	18.10	13.8	35.6	Rivet
	520SO		○	○			2.00	2.00	21.7/19.9	15.4	30.5	Clip/Rivet
	530UWR			Silver Color Only				2.20	2.30	22.7	18.6	41.2
<b>Vintage Bike</b>	532GSV	XW	○				2.40	2.40	24.5	22.3	43.0	Rivet
	630GSV		○				2.40	2.40	25.1	29.5	48.0	Rivet

Off-Road Series	RK Model	Seal Type	STD	GB	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Motocross</b>	420MXZ	NON SEAL	○	○			1.80	1.45	17.1	7.8	22.2	Clip
	428MXZ1		○	○			2.00	2.00	20.1	10.0	27.0	Clip
	520KXZ		○	○			2.00	2.00	19.3	14.6	35.0	Clip
<b>Premium Motocross</b>	420MXZ4	NON SEAL		○			1.80	1.45	17.1	7.8	22.2	Clip
	428MXZ4			○			2.00	2.00	20.1	10.0	28.5	Clip
	520MXZ5			○	○		2.00	2.00	19.2	13.9	37.8	Clip
<b>Enduro</b>	420MXU2	U		○			1.80	1.45	17.1	7.9	22.2	Clip
	428MXU			○			2.00	2.00	20.2	10.0	27.0	Clip
	520MXU		UW		○			1.80	2.00	19.2/18.1	13.8	35.6
520EXW	XW	○		○		2.20	2.20	22.0/20.8	16.8	34.3	Clip/Rivet	

Sprint Race Series	RK Model	Seal Type	STD	GB	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Sprint Race</b>	520XRU	UW		○			2.20	2.00	18.8	15.6	40.0	Rivet
	520RUWR			○			2.00	2.00	18.4	14.7	35.3	Rivet
	520TRU			○			2.00	2.00	18.4	13.7	26.9	Rivet
	415SHRU	U		○			1.45	1.45	15.4	6.9	21.4	Clip

Drag Race Series	RK Model	Seal Type	STD	GB	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Drag Race</b>	530DR	NON SEAL	○				2.60	2.40	24.7	22.50	46.0	Clip
	530PRODR		○				3.10	2.60	26.5/25.0	23.70	52.3	Clip/Rivet

ATV Series	RK Model	Seal Type	STD	GB	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>ATV</b>	520SO	XW	○	○			2.00	2.00	21.7/19.9	15.4	30.5	Clip/Rivet
	520EXW		○	○			2.20	2.20	22.0/20.8	16.8	34.3	Clip/Rivet

Non-sealed Series	RK Model	Seal Type	STD	GS	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Premium Heavy Duty</b>	420MS	NON SEAL	○				1.80	1.45	16.7	7.8	18.7	Clip
	530KS		○				2.00	2.00	21.9	17.0	31.6	Clip
<b>Heavy Duty</b>	415HSB	NON SEAL	○	○*1	○		1.45	1.45	14.6	7.0	18.3	Clip
	428HSB		○	○*1	○		2.00	2.00	20.3	10.4	24.2	Clip
	520H		○	○*1	○		2.30	2.30	19.7	16.7	34.3	Clip
	525H		○				2.30	2.30	21.3	17.4	34.3	Clip
	530H		○				2.30	2.30	22.9	18.8	34.3	Clip
<b>Standard</b>	420SB	NON SEAL	○	○*1	○		1.45	1.45	16.2	7.5	18.5	Clip
	428SB		○				1.45	1.45	18.9	8.8	19.1	Clip
	520		○				2.00	2.00	18.5	15.0	29.4	Clip
	525		○				2.00	2.00	19.9	16.0	29.4	Clip
	530		○				2.00	2.00	21.7	17.0	29.4	Clip

On-Road Series	RK Model	Seal Type	STD	GS	Color	BL	Plate Thickness		CL Pin Length	Weight [g/L]	Tensile [kN]	Con Link Type
							Inner	Outer				
<b>Economic Sealed Chain</b>	428KRO	O	○	○*1	○		1.80	1.80	21.6/20.2	11.7	24.0	Clip/Rivet
	525KRO		○	○*1			2.40	2.30	22.9	19.6	38.3	Rivet
	530KRO		○	○*1			2.40	2.30	24.7	20.7	38.3	Rivet

Remarks \*1 Gold Plating on Outer Plate Only